

Cotto Moderno

8" Hex Porcelain / 3x10 Ceramic Wall / 2x16 Porcelain



03COM018HC



03COM018H



03COM028HC



03COM028H



03COM01310U



03COM02310U



03COM01216



03COM02216



03COM038HC



03COM038H



03COM048HC



03COM048H



03COM03310U



03COM04310U



03COM03216



03COM04216



Tile: 2x16 - 8" Hex
Wall Tile: 3x10
Mosaic: N/A
Trim: N/A

For more information
and images:



Cotto Moderno

Porcelain / Ceramic



Technical Characteristics

Test Item	Test Method	Test Result - Porcelain	Test Result - Ceramic
Breaking Strength	ASTM C648	> 400 lbf	N/A
Bond Strength	ASTM C482	> 200 lbf	N/A
Thermal Shock Resistance	ASTM C484	Unaffected	Unaffected
Chemical Resistance	ASTM C650	Resistant	Resistant
Water Absorption	ASTM C373	< 0.50%	3.0% - 7.0%
Scratch Hardness	Mohs Scale	7	6
Facial Dimension	ASTM C499	± 0.25%	Compliant
Range of Thickness (in)	ASTM C499	0.3	0.3
Warpage - Diagonal	ASTM C485	± 0.20%	± 0.30%
Wedging	ASTM C502	± 0.50%	± 0.40%
Crazing Resistance	ASTM C424	No Crazing	No Crazing
DCOF (Wet)	ANSI A326.3	0.60-0.70	N/A

Nominal Size	Actual Size	Thickness	Finish	Rectified
2" x 16" Flat Long Brick	1.97" x 15.74"	8.0 mm	Unpolished	-
8" Chevron Hex	7.87" Diagonal	7.0 mm	Unpolished	-
8" Flat Hex	7.87" Diagonal	7.0 mm	Unpolished	-
3" x 10" Undulating Wall Brick *	2.76" x 10.24"	7.0 mm	Unpolished	-

* This size tile is Ceramic and for Wall use only.

