

---

# State of Grace

---

## Porcelain Stone®

### Features and Benefits

- Coordinates with Crossville Porcelain Slabs
- One shade of white in Unpolished and Satin finishes.
- Trim includes 4 x 24 Single Bullnose, 6 x 12 Covebase and 2 x 12 Covebase
- All field tile is rectified with a recommended minimum 3mm grout joint

### Color Palette



**GRC01** ▶ State of Grace UPS



**GRC01** ▶ State of Grace Satin



**GRC01** ▶ State of Grace 24 x 48 UPS



# State of Grace


## Porcelain Stone®




### Sizes



24 x 48




24 x 24



12 x 24



6 x 24



12 x 12



2.5 x 12 Chevron Left and Right



3x6 Picket



3 x 6

**3 x 3 Hex Mosaics**  
UPS Finish  
Mesh mounted on a 276mm x 296mm sheet



**2 x 2 Mosaics**  
UPS Finish  
Mesh mounted on a 298mm x 298mm sheet



**Herringbone Mosaic**  
UPS Finish  
Mesh mounted on a 306mm x 272mm sheet

### Sizes & Finishes

#### Field Tile - Rectified

Nominal (in)	Actual (mm)	Thickness (mm)	Grout Joint (mm)	UPS Finish	Satin Finish
3 x 6	72 x 147	9.5	3	GRC01.10306UPS	GRC01.10306SAT
3 x 6 Picket	72 x 146	9.5	3	GRC01.136UPSPCK	GRC01.136SATPCK
6 x 24	147 x 597	9.5	3	GRC01.10624UPS	GRC01.10624SAT
2.5 x 12 Chevron Right	64 x 305	9.5	3	GRC01.10312UCVR	GRC01.10312SCVR
2.5 x 12 Chevron Left	64 x 305	9.5	3	GRC01.10312UCVL	GRC01.10312SCVL
12 x 12	297 x 297	9.5	3	GRC01.11212UPS	GRC01.11212SAT
12 x 24	297 x 597	9.5	3	GRC01.11224UPS	GRC01.11224SAT
24 x 24	597 x 597	9.5	3	GRC01.12424UPS	
24 x 48	597 x 1197	10.5	3	GRC01.12448UPS	

All field tile is rectified.  
Crossville recommends a minimum 3mm grout joint.

#### Mosaics

Nominal (in)	Actual (mm)	Sheet Size (mm)	Thickness (mm)	Grout Joint (mm)	UPS Finish
3 x 3 Hexagon	77 x 88	296.1 x 276	9.5	3	GRC01.13HEXUMOS
2 x 2 Square	47 x 47	298 x 298	9.5	3	GRC01.10202UMOS
Herringbone Mosaic	33 x 98	206.18 x 371.6	9.5	3	GRC01.1HBUPSMOS

#### Coordinating Trim

Nominal (in)	Actual (mm)	Thickness (mm)	Grout Joint (mm)	UPS Finish	Satin Finish
4 x 24 Single Bullnose	96 x 597	9.5	3	GRC01.10424BNS	GRC01.10424SABN
2 x 12 Cove Base	45 x 297	9.5	3	GRC01.10212CB	-
1-1/2 x 12 Chair Rail†	30 x 297	9.5	3	-	GRC01.11512SCR
3 x 12 Crown Molding†	75 x 297	9.5	3	-	GRC01.10312CM
6 x 12 Base Molding†	150 x 297	9.5	3	-	GRC01.10612BM

† Globally Sourced - Hydroteect™ not available



#### Product Performance


	UPS	Satin	
Breaking Strength	>450 lbf	>450 lbf	ASTM C648
Bond Strength	>200 psi	>200 psi	ASTM C482
Chemical Resistance	Unaffected	Unaffected	ASTM C650
Frost Resistance	Resistant	Resistant	ASTM C1026
Water Absorption	<0.50%	<0.50%	ASTM C373
Scratch Hardness	7	5	Mohs Scale

#### Wet Dynamic Coefficient of Friction Range

UPS	0.42 - 0.52	ANSI A326.3
SAT	0.31 - 0.41	ANSI A326.3

#### Shade & Texture Index

State of Grace has a shade variation of V2.



This porcelain tile product is produced with a V2 variation. Expect that the amount of color and texture on each piece may vary slightly. Inspect the product upon delivery and for best results, blend tile from several cartons during installation.

#### Get Planked!

Our Porcelain Stone® products are available in popular plank shapes with no minimum order and quick fulfillment. See website for more details and sizes.



## Application Areas

Finish	Interior Floors (dry)	Interior Walls (wet/dry)	Exterior Walls	Interior Floors (Standing water/shower floors)	Exterior/Paving	Pool/Fountain Full Lining**	Water Line Pool/Fountains
UPS	✓	✓	✓	Mosaic Only*		✓	✓
SAT	✓	✓	✓			✓	✓

\* 4" or less in both length and width. UPS or UP mosaics

NOTE: Trim applications will differ from field tile applications for the same series.

\*\* Excludes mesh mounted mosaics. Crossville recommends face mounted or edge mounted mosaics for fully submerged applications. Contact your Crossville sales representative for more information.

For more information on ANSI- A362.3 visit our website at <https://www.crossvilleinc.com/Resources/Tile-101/DCOF?tab=1>

## Recommended Use

State of Grace UPS is recommended for interior floors, interior walls, countertops, exterior walls, pool waterlines and full linings† in both residential and commercial applications. State of Grace UPS is not recommended for exterior horizontal surfaces or exterior paving. **The satin finish is not recommended for wet areas where standing water may occur.** See [CrossvilleInc.com](http://CrossvilleInc.com) for detailed installation instructions.

† Excludes mesh mounted mosaics..

## Wet area use for State of Grace mosaics

Crossville® produces the State of Grace 3 x 3 hexagon and 2 x 2 mosaics with the Cross-Sheen® (UPS) finish. The ANSI A326.3 wet Dynamic COF of State of Grace is ≥ .42. Their small sizes ensures frequent grout joints which provides traction and drainage. Crossville cannot control situations involving incorrect installation, improper slope to the drain for elimination of standing water and poor surface cleaning.

This information is provided so that customers may make a realistic and informed decision when comparing State of Grace to other tile products in wet area environments, such as residential/commercial bathrooms, showers, and interior pool decks.

## Care and Maintenance

Regular cleaning is the best way to keep State Of Grace tile looking good for years to come. Use clean, hot water (combined with a household cleaner for more aggressive cleaning). Rinse thoroughly and dry with a soft cloth. No waxes are needed.

**State Of Grace satin requires a grout release prior to grouting.** More information regarding the care and maintenance of Crossville® products is available at [CrossvilleInc.com](http://CrossvilleInc.com).

## Our Warranty

Crossville Inc. guarantees that its products will meet or exceed the performance specifications outlined in ANSI A137.1-2022 and in the performance data section of the Crossville, Inc. general product catalog. For complete details check our website at [CrossvilleInc.com](http://CrossvilleInc.com).

*Information listed here is subject to change. Please refer to [CrossvilleInc.com](http://CrossvilleInc.com) for the latest, most accurate information.*

## ▶▶ Crossville® Sample Express

Visit the website to learn more:  
**[CrossvilleInc.com/Products/State-of-Grace](http://CrossvilleInc.com/Products/State-of-Grace)**

### Loose Samples

Sizes may vary depending on product series  
Max. of 4 large field tile per order

### Standard Shipping

FedEX Ground

## National Accounts

For over 20 years we have been offering Porcelain tile to commercial customers at National Accounts pricing programs with special discounts. The National Accounts department provides materials forecasting, sales support and samples.

## CrossvilleInc.com

If you want a better idea of what Crossville tile would look like in a particular room setting, simply visit our website and click on Cross-Vision. This powerful software tool allows you to visualize different types of Crossville tile. In addition, you'll find comprehensive information about Crossville's entire portfolio of products. You can also learn about the latest styles and trends from industry experts, download detailed care and maintenance instructions for our various products, or browse electronic versions of Crossville's product brochures. So whether you need information about Crossville products or tile in general, please visit us at [CrossvilleInc.com](http://CrossvilleInc.com).

## Trade Organizations



## Environmentally Aware

