

Stones At Large

12x24 Porcelain



03SAL031224 (unpolished)
03SAL031224PO (polished)



03SAL021224 (unpolished)
03SAL021224PO (polished)



03SAL041224 (unpolished)
03SAL041224PO (polished)



2x2 Mosaic



Leaf Mosaic



Tile: 4x12 - 12x24 - 24x48 - 48x48

Mosaics: 2x2 - 15x12 Leaf

Trim: 4x24 Bullnose

Not all colors available in all sizes or finishes

For more information
and images:





Technical Characteristics

Test Item	Test Method	Test Result
Water Absorption	ISO 10545-3	< 0.5%
Breaking Strength	ISO 10545-4	≥ 35 N/mm ²
Facial Dimension	ISO 13006	± 0.8 mm
Warpage - Diagonal	ISO 13006	± 1.8 mm
Wedging	ISO 13006	± 0.8 mm
Frost Resistance	ISO 10545-12	Resistant
DCOF	ANSI A326.3	< 0.42 (Polished); 0.42-0.52 (Unpolished)

Nominal Size	Actual Size	Thickness	Finish *	Rectified
4" x 12"	3.82" x 11.81"	8.5 mm	Polished	Yes
12" x 24"	11.81" x 24.13"	8.5 mm	Polished or Unpolished	Yes
24" x 48"	23.56" x 47.19"	10.0 mm	Polished or Unpolished	Yes
48" x 48"	47.05" x 47.05"	10.0 mm	Polished or Unpolished	Yes
2" x 2" Mosaic	11.73" x 11.73"	8.5 mm	Unpolished	-
Leaf Mosaic	14.96" x 12.2"	8.5 mm	Unpolished	-
4" x 24" Bullnose	3.82" x 24.13"	8.5 mm	Polished or Unpolished	-

* Polished finish is only recommended for residential and light commercial use due to low Mohs hardness scratch resistance and increased susceptibility to scratching compared to matte surface. It is not recommended for wet areas where standing water may occur or for exterior horizontal and/or walking surfaces.

Installation Note: The TCNA recommends rectangular shape tile be installed with maximum of 33% offset in order to resolve any possible lippage from one tile to the next.

