Forge 12x24 Color Body Porcelain













Herringbone Mosaic

Brick Mosaic









Extend Mosaics

15FORRUS811EM

2x2 Mosaic



QuickSHIP (noted colors only)

3x12 - 12x24 Tile:

Mosaics: 1x3 Herringbone - 2x2

Special Order

Tile: 12x24

Mosaics: 1.5x3 Brick - 2x2 - 8x11 Extend 3x24 Bullnose - 6x12 Cove Base Trim:

Not all colors available in all sizes or finishes

For more information and images: 📭 🕍













Technical Characteristics

Characteristic	Test Method	Calibrated		Rectified		Malaaa
		Minimum	Maximum	Minimum	Maximum	- Value
Nominal Size		- 3%	+ 3%	- 3%	+ 2%	Compliant
Caliber Range	ASTM C499	- 0.5% or - 0.08 in	+ 0.5% or + 0.08 in	- 0.25% or - 0.03 in	+ 0.25% or + 0.03 in	Compliant
Thickness		N/A	Range: 0.4 in	N/A	Range: 0.4 in	Compliant
Wedging	ASTM C502	- 0.5% or - 0.08 in	+ 0.5% or + 0.08 in	- 0.25% or - 0.03 in	+ 0.25% or + 0.03 in	Compliant
Warpage Edge	ASTM C485	- 0.75% or - 0.09 in	+ 0.75% or + 0.09 in	- 0.40% or - 0.05 in	+ 0.40% or + 0.05 in	Compliant
Warpage Diagonal		- 0.5% or - 0.08 in	+ 0.5% or + 0.08 in	- 0.40% or - 0.07 in	+ 0.40% or + 0.07 in	Compliant
		All Porcelain Tiles				
Water Absorption	ASTM C373	≤ 0.5%				≤ 0.5%
Breaking Strength	ASTM C648	Average ≥ 250 lbf; Individual ≥ 225 lbf				≥ 350 lbf avg
Bond Strength	ASTM C482	≥ 50 psi				≥ 100 psi
Resistance to Freeze/ Thaw Cycling	ASTM C1026		Resistant			
Chemical Resistance	ASTM C650		Unaffected			
Stain Resistance	ASTM C1378	As Reported				Unaffected
Dynamic Coefficient of Friction	DCOF (Wet)	Requires a r	> 0.42			
VOC	No VOC					

Nominal Size	Actual Size	Thickness	Finish	Rectified
3" x 12"	2.77" x 11.81"	9 mm	Matte	-
12" x 24"	11.81" x 23.62"	9 mm	Matte	-
1" x 3" Herringbone Mosaic	11.75" x 11.75"	9 mm	Matte	-
1.5" x 3" Brick Mosaic	11.81" x 11.81"	9 mm	Matte	-
2" x 2" Mosaic	11.75" x 11.75" -OR- 11.81" x	9 mm	Matte	-
	11.81" sheet*			
8" x 11" Extend Mosaic	8.27" x 11.02" (2" x 6.5" piece)	9 mm	Matte	-
3" x 24" Bullnose	2.83" x 23.62"	9 mm	Matte	-
6" x 12" Cove Base	5.91" x 11.81"	8.5 mm (7 mm flat part)	Matte	-

^{*} Depending on color. See QR code for details.

All tile is subject to variations in technical specifications and performance due to the inherent variables in the raw materials and production process. It is understood that test results on a particular product may vary slightly from tile to tile and from test to test. Test results are not guarantees of minimum or maximum thresholds of performance.



