

Travertino

12x24 Glazed Porcelain

mosaic 
Products. Design. Solutions.



15SQTWHI1224



15SQTIVO1224



2x2 Mosaic



15SQTSIL1224



15SQTSAN1224



Tile: 12x24
Mosaic: 2x2
Trim: 3x24 Bullnose
Outdoor: 20mm 24x24 (IVO only)

Not all colors available in all sizes

*For more information
and images:*



Technical Characteristics

		Porcelain Tile Specification		
Characteristic	Test Method	Calibrated	Rectified	Value
Nominal Size	ASTM C499	+ 3.00%	- 3.00% ÷ + 2.00%	Compliant
Caliber Range		±0.50% or ±0.08 in (±2.0 mm)	±0.25% or ±0.03 in (±0.8 mm)	Compliant
Thickness		Range: 0.04 in (1.02 mm)		Compliant
Wedging	ASTM C502	±0.50% or ±0.08 in (±2.0 mm)	±0.25% or ±0.03 in (±0.8 mm)	Compliant
Warpage Edge	ASTM C485	±0.75% or ±0.09 in (±2.3 mm)	±0.40% or ±0.05% (±1.3 mm)	Compliant
Warpage Diagonal		±0.50% or ±0.08 in (±2.0 mm)	±0.40% or ±0.07% (±1.8 mm)	Compliant
Water Absorption	ASTM C373	≤ 0.5%		≤ 0.5%
Breaking Strength	ASTM C648	Average ≥ 250 lbf; Individual ≥ 225 lbf		≥ 350 lbf avg
Bond Strength	ASTM C482	≥ 50 psi		≥ 100 psi
Freeze Resistance	ASTM C1026	As Reported		Resistant
Thermal Shock Resistance	ASTM C484	As Reported		Resistant
Chemical Resistance	ASTM C650	As Reported		Unaffected
Stain Resistance	ASTM C1378	As Reported		Unaffected
Dynamic Coefficient of Friction (DCOF)	ANSI A326.3	Subject to the project		≥ 0.42 Wet

Nominal Size	Actual Size	Thickness	Finish	Rectified
12" x 24"	11.75" x 23.62"	8 mm	Matte	-
24" x 24" Paver	23.62" x 23.62"	20 mm	Matte	Yes
2" x 2" Mosaic	11.75" x 11.75"	8 mm	Matte	-
3" x 24" Bullnose	2.87" x 23.62"	8 mm	Matte	-

All tile is subject to variations in technical specifications and performance due to the inherent variables in the raw materials and production process. It is understood that test results on a particular product may vary slightly from tile to tile and from test to test. Test results are not guarantees of minimum or maximum thresholds of performance.