

Onyx Unique

12x24 Color Body Glazed Porcelain




45ONYUNI1224 (natural)



45ONYUNI1224P (polished)



1x4 Goccia



1.5x1.5 Mosaic



4x16 (matte or glossy)



4x16 Scolpito



- Tile: 4x16 Matte - 12x24 - 24x48 - 48x48
- Wall Tile: 4x16 Glossy - 4x16 Scolpito
- Mosaic: 1x4 Goccia - 1.5x1.5
- Trim: 3x12 Bullnose

For more information
and images:



Technical Characteristics

Test Item	Test Method	Test Result			
		Natural	Polished	Matte	Glossy
Breaking Strength	ASTM C648	≥ 275 lbf		≥ 250 lbf	
Scratch Hardness	Mohs	7	5	7	5
Stain Resistance	ASTM C1378	Class A	Class E	Class A	Class E
Chemical Resistance	ASTM C650-04	Class A	Class E	Class A	Class E
Frost Resistance	ASTM C1026	Resistant		N/A	
Water Absorption	ASTM C373	≤ 0.5%		≤ 7%	
DCOF (Wet)	ASTM C1028	≥ 0.42%	< 0.42%	≥ 0.42%	N/A

Nominal Size	Actual Size	Thickness	Finish	Rectified
4" x 16" **	3.98" x 15.94"	7.0 mm	Glossy	-
4" x 16"	3.98" x 15.94"	7.0 mm	Matte	-
4" x 16" Scolpito **	3.98" x 15.94"	8.0 mm	Matte	-
12" x 24"	11.70" x 23.50"	8.0 mm	Natural or Polished	Yes
24" x 48"	23.50" x 47.13"	8.5 mm	Natural or Polished	Yes
48" x 48" *	47.13" x 47.13"	7.0 mm	Natural or Polished	Yes
1" x 4" Goccia Mosaic	7.59" x 10.0"	8.0 mm	Natural or Polished	Yes
1.5" x 1.5" Mosaic	11.73" x 11.73"	8.0 mm	Natural or Polished	Yes
3" x 12" Bullnose	2.87" x 11.65"	8.0 mm	Natural or Polished	Yes

* Noted size is made in Brazil and is not Color Body Porcelain.

** Noted sizes are Glazed Ceramic and are meant for wall installations only.

All tile is subject to variations in technical specifications and performance due to the inherent variables in the raw materials and production process. It is understood that test results on a particular product may vary slightly from tile to tile and from test to test. Test results are not guarantees of minimum or maximum thresholds of performance.

Installation Note: The TCNA recommends rectangular shape tile be installed with maximum of 33% offset in order to resolve any possible lippage from one tile to the next.