











TECH DATA

									
Finish	Freeze Resistant	Shade Variation	Color Body	Water Absorption	Stain Resistant	DCOF AcuTest	Chemical Resistant	Breaking Strength	Mohs Hardness
NAT	Resistant	V4	N/A	≤0.5%	Class A	≥0.42	Class A	≥ 275 lbf	8

PACKING INFO

PRODUCT SIZE INCHES	ACTUAL SIZE	THICKNESS MM	LBS/ CARTON	PCS/ CARTON	SF/ CARTON	SF/ PALLET	LBS/ PALLET	CARTON/ PALLET	FACES
1x6 Mosaic	11.77 x 11.77	8.00	36.00	10	9.79	352.44	1,296.00	36	10
2x2 Mosaic	11.73 x 11.73	8.00	39.99	10	9.57	344.52	1,439.64	36	10
2.5x15	2.51 x 14.51	8.00	71.00	20	4.30	258.00	4,260.00	60	10
12x24	11.70 x 23.50	8.00	52.09	7	13.37	748.72	2,917.01	56	40
24x48	23.50 x 47.13	10.00	76.02	2	15.38	307.60	1,520.40	20	25

For reference only.

AREAS OF USAGE

Classification	Reference Category	Suitable
Interior, Dry	ID	√
Interior, Wet	IW	√
Interior, Wet Plus	IW+	√ 1x6 2x2 2.5x15
Exterior, Wet	EW	
Oils/Greases	O/G	

FORMATS



24x48



12x24

GROUT JOINT

The recommended grout joint:

1/8" RECT



06x12 COVE BASE



03x12 BULLNOSE



12x12



12x12



2.5x15