Black			
TILE MATERIAL			Porcelain
POLISH/SHEEN			Low (Matte), High (Glossy)
PORCELAIN ENA	AMEL INSTITUTE RAT	ING	2
Mohs Hardness S	cale Rating		3
OUTDOOR USE:	1=Yes 0=No		1
TILE DEPTH (IN)	SHEET DEPTH (IN)		0.25
DYNAMIC COEFI	FICIENT OF FRICTIO	N	0.310
TILE USE			Floor and Wall

9.04

Case

10

Somertile Sq. Ft. Per UOM

Somertile Unit of Measure

Somertile Pieces Per UOM

Gray	Ĭ	Ĭ.		
TILE MATERIAL			Porcelain	
POLISH/SHEEN			Low (Matte), High (Glossy)	
PORCELAIN ENAMEL INSTITUTE	RATING		2 (Matte), 3 (Glossy)	
Mohs Hardness Scale Rating			3 (Matte), 4 (Glossy)	
OUTDOOR USE: 1=Yes 0=No			1	
TILE DEPTH (IN)/SHEET DEPTH	(IN)		0.25	
YNAMIC COFFEIGIENT OF FRIC	CTION		0.310	

Floor and Wall

9.04

Case

10

TILE USE

Somertile Sq. Ft. Per UOM

Somertile Unit of Measure

Somertile Pieces Per UOM

ight (	Gray
--------	------

TILE MATERIAL	Porcelain
POLISH/SHEEN	Low (Matte), High (Glossy)
PORCELAIN ENAMEL INSTITUTE RATING	3
Mohs Hardness Scale Rating	4
OUTDOOR USE: 1=Yes 0=No	1
TILE DEPTH (IN)/SHEET DEPTH (IN)	0.25
DYNAMIC COEFFICIENT OF FRICTION	0.310
TILE USE	Floor and Wall
Somertile Sq. Ft. Per UOM	9.04
Somertile Unit of Measure	Case
Somertile Pieces Per UOM	10

W	hite	

TILE MATERIAL

POLISH/SHEEN	Low (Matte), High (Glossy)
PORCELAIN ENAMEL INSTITUTE RATING	2
Mohs Hardness Scale Rating	3
OUTDOOR USE: 1=Yes 0=No	1
TILE DEPTH (IN)/SHEET DEPTH (IN)	0.25
DYNAMIC COEFFICIENT OF FRICTION	0.310
TILE USE	Floor and Wall
Somertile Sq. Ft. Per UOM	9.04
Somertile Unit of Measure	Case
Somertile Pieces Per UOM	10

Porcelain